PRODUCT SPECIFICATIONS FOR CB10

WEIGHTS	
Operating Weight	20945.0 lb
Standard Operating Weight with Cab	21407.0 lb
Maximum Operating Weight with ROPS	22564.0 lb
Standard Operating Weight with ROPS	20945.0 lb
Maximum Operating Weight with Cab	23171.0 lb
OPERATING SPECIFICATIONS	
Standard Compaction Width	67.0 in
Static Linear Load	160.0 lb/in
Travel Speed - Maximum	7.5 mile/h
Maximum Compaction Width	73.0 in
ENGINE	
Gross Power	131.0 HP
Engine Model	Cat C4.4 with ACERT Technology
DIMENSIONS	
Overall Length	177.0 in
Wheel Base	130.0 in
Height - With ROPS/FOPS	117.0 in
Overall Width	73.0 in
Drum Diamotor	47 O in

VIBRATORY S	SYSTEM
-------------	--------

Drum Width	67.0 in
Vibration Selection	Independent per drum, front only, rear only, both
Nominal Amplitude - High	0.042 in
Centrifugal Force per Drum - Minimum	6092.0 lb
Centrifugal Force per Drum - Maximum	28977.0 lb
Nominal Amplitude - Low	0.013 in

SERVICE REFILL CAPACITIES

Fuel Tank Capacity	50.0 gal (US)
Water Spray Tank Capacity	211.0 gal (US)

CB10 OPTIONAL EQUIPMENT

AIR CONDITIONING

AIR SUSPENSION SEAT W/HEAT

BIO-DEGRADEABLE OIL

CAT COMPACTION CONTROL

COMPACTION METER VALUE

EDGE CUTTER

FIVE AMPLITUDE VIBRATORY SYSTEM

FREEZE PROTECTION KIT (WATER SPRAY)

HALOGEN LIGHTS WITH DRUM EDGE LIGHTING

HIGH AMBIENT COOLING SYSTEM

HIGH INTENSITY DISCHARGE LIGHTS

LED LIGHTS

MACHINE TO MACHINE COMMUNICATION

MIRRORS

OSCILLATION TECHNOLOGY

PRODUCT LINK

ROADING LIGHTS

RECORDING MODULE

ROPS/FOPS CAB

TEMPERATURE GAUGE

TWO AMPLITUDE, TWO FREQUENCY VIBRATORY SYSTEM

WARNING BEACON

WATER DISTRIBUTION MATS

VERSA VIBE VIBRATORY SYSTEM