

# PRODUCT SPECIFICATIONS FOR PM620

---

## CUTTING SYSTEM

---

<b>Milling Width</b>	2010.0 mm
<b>Number of Bits</b>	178
<b>Rotor Speeds</b>	100 / 109 / 118 rpm
<b>Maximum Milling Depth</b>	330.0 mm

---

## POWER TRAIN

---

<b>Rated Power</b>	470.0 kW
<b>Maximum Milling Speed</b>	100.0 m/min
<b>Maximum Travel Speed</b>	5.9 km/h
<b>Engine</b>	Cat C18

---

## WEIGHTS

---

<b>Operating Weight</b>	33330.0 kg
<b>Transport Weight</b>	29400.0 kg

---

## DIMENSIONS

---

<b>Operating Width</b>	2.79 m
<b>Maximum Truck Clearance</b>	4.86 m
<b>Transport Height</b>	3.0 m
<b>Minimum Right Cutting Radius</b>	2.0 m
<b>Height - Canopy</b>	4.05 m
<b>Conveyor Swing</b>	60 degrees from center

---

<b>Conveyor Swing</b>	00 degrees from center
<b>Minimum Left Cutting Radius</b>	2.0 m
<b>Transport Width</b>	2.5 m
<b>Operating Length - Conveyor Up</b>	14.52 m
<b>Transport Length</b>	12.43 m

---

---

#### SERVICE REFILL CAPACITIES

---

<b>Cooling System</b>	85.0 l
<b>Engine Oil</b>	65.0 l
<b>Fuel Tank</b>	1108.0 l
<b>Diesel Exhaust Fluid (DEF) Tank</b>	47.0 l
<b>Water Spray System Tank</b>	3400.0 l
<b>Hydraulic Tank</b>	113.0 l

---

## PM620 OPTIONAL EQUIPMENT

### POWER SUN CANOPY

Windscreens for Power Canopy